

## **VERTICAL COMPACTOR**

**VCH SERIES** 

Four side loading options ...five container options...all in one unit! The VCH line of vertical compactors are designed to allow customized loading options along with versatility in container sizes allowing for volume growth without changing compactors.


## **FEATURES**

- Sliding feed door is designed to eliminate trash from gathering on top of press head
- No hydraulic lines attached to the container eliminates the need for driver to exit the truck, saving time and money
- Eliminates the mess of spillage when emptying the container
- · Rugged construction provides long life
- Compaction ratios average 4 to 1 depending on material mix
- Loading capabilities from all 4 sides allowing user front, rear or side feed loading and can be combined with an open chute or thru-the-wall access for customized loading access
- Load from the ground, off a dock or through the wall
- Feed heights starting at 40 ¼"
- Door safety interlock
- · Highly visible "Safe to Haul" light
- Removable key for authorized operator usage
- ANSI Z245.21 compliant

SPECIFICATIONS	
Clear Top Opening	37 ¼" L x 38" W
Cycle Time	35 seconds
Compaction Force	24,650 lbs
Ram Penetration	10"
Ram Face Dimensions	48" W x 48" L
Ram Face Pressure	11 psi
Motor	5 HP

208/230/460 VAC 60 Hz Three Phase





TYPE	Α	В	С	D	WEIGHT
3 YD FL	100"	79"	40 1⁄4"	115 1⁄4"	3892 lbs
4 YD FL	100"	79"	40 1⁄4"	121 ¼"	3973 lbs
4 YD RL	82"	100"	46 1⁄4"	121 ¼"	4050 lbs
5 YD FL	100"	79"	56 1/4"	131 ¼"	4183 lbs
6 YD FL	100"	95 ½"	56 1/4"	131 ¼"	4294 lbs
8 YD FL	100"	95 ½"	74"	150"	4510 lbs

Due to continual product improvement Compactors Inc. reserves the right to change specifications without notice. The information and pictures used in the document are for illustrative purposes only.



Voltage