

## **HORIZONTAL BALER – MODEL HE-60 SERIES**

The "HE Series" Horizontal Baler is designed with our largest clear top opening, almost 25% larger than our largest 72" Horizontal Baler and can be used with our without a conveyor system.

Designed for ease of installation, operation and maintenance the baler can operate manually or automatically with photo electric cell control. The HE-60 is ideal for warehouses, users baling waste paper, corrugated, newsprint, office white, plastics, foam rubber, light aluminum and other recyclables without pre-conditioning or fluffing required.



## **FEATURES**

- ANSI Z245.2 Compliant All compactors meet or exceed ANSI Z245.2 safety standards
- UL/CUL Listed Control Panels
- UHMW Ram Shoes Adjustable to assure straight tracking and readily replaceable, should the need arise
- · Oil Sight Gauge Oil level at a glance
- · Heavy Duty Controls NEMA 4 rated pushbutton controls with key-lockable start switch
- Automatic Single Cycle Operation

## **SPECIFICATIONS**

- Nominal Bale Size 48" L x 60" W x 30" H
- Clear Top Opening (W x L) 60" x 35 ½"
- Bale Weight Up to (OCC) 1,300 lbs
- Throughput (OCC) 2.5 bales/hr
- Cycle Time (No Load) 47 seconds
- Platen Force 120,600 lbs normal | 140,800 lbs max
- Platen Face Pressure 67 psi normal | 78.2 psi max
- Motor (3 Phase) 20 hp
- Pump Capacity 37.5 gpm
- Hydraulic Reservoir Capacity 107 gallons
- Hydraulic Cylinder Bore Diameter 8"
- Hydraulic Cylinder Stroke 84"
- Hydraulic Rod Diameter 5"
- Operating Pressure 2,400 psi normal | 2,800 psi max

## **HE SERIES DIMENSIONS**

	Overall Height w/ Provided Hopper	Overall Width	Overall Length w/ Door Open & Provided Conveyor	Unit Weight
HE-60	7' 10"	6' 3 ½"	22' 3"	15,200 lbs
HE-60-M	10' 8"	6' 3 ½"	32' 8"	16,850 lbs
HE-60-MP	10' 8"	6' 3 ½"	43' 5 7/8"	17,200 lbs

Due to continual product improvement Compactors Inc. reserves the right to change specifications without notice. The information and pictures used in the document are for illustrative purposes only.

