

VERTICAL BALER

MODEL VMAX26

This heavy-duty baler delivers greater compact force while still only taking minimal space. Designed for use in retail stores, manufacturing plants, warehouses, distribution centers or any location producing refuse paper, plastic and non-ferrous metals.

PERFORMANCE

- Nominal Bale Size 42" x 45" x 72"
- Bale Weight Up to 2000 lbs. OCC
- Bale Volume 79 cu. ft.
- Number of Bale Tie Slots 7
- Feed Opening 26"
- Compact Force lbs. Normal/Maximum 125,663/150,798
- Platen Pressure 42 PSI
- Average Cycle Time 55 Seconds
- Loading Height 54.5"
- Full Bale Switch/Light Standard


HYDRAULIC/ELECTRICAL

- Motor HP 10 Submersible
- Voltage 3 Phase 208, 230, 480
- Full Load Amps 32A, 28A, 14A
- **Twin Pump GPM** 16/4
- Normal System Pressure PSI 2500
- Maximum System Pressure PSI 3000
- Cylinder Bore 8" x 48"
- Hydraulic Tank-Capacity Gallons 38

AVAILABLE OPTIONS

- Slotted Front Door
- · Single Phase Power Unit
- · Rear Wire Guides
- International Safety Option With CAT3
- Regen Circuit
- IntelliBALE with 10,000 lb. Load Cells
- Oil Heater
- Weather Proof Package





Due to continual product improvement Compactors Inc. reserves the right to change specifications without notice. The information and pictures used in the document are for illustrative purposes only. Compactors Inc. equipment is ETL/CSA certified with UL listed controls and meets or exceeds ANSI standard Z245.5.

