

VERTICAL BALER

MODEL V74XHD

Our standard V74XHD (heavy duty) features a 10 HP High Efficiency Power Unit. Offering a 72"wide feed opening and a 40" deep chamber, this unit is perfect for white-goods boxes for which penetration is required. It has a 60" stroke cylinder and begins compaction closer to the bottom of the chamber for more lbs. per cubic foot and less material spring-back.

Ideal for: • Grocery Stores • Home Retailers • Pharmacies • Big Box Retailers • National Accounts • Commissaries • Warehouses • Distribution Centers • Hospitals, Schools & Universities • Recyclers

PERFORMANCE


- **Nominal Bale Size** 72" x 40" x 48"
- Bale Weight Up to 1700 lbs. OCC
- Bale Volume 80 cu. ft.
- Number of Bale Tie Slots 7
- Compact Force lbs 84,667
- Platen Pressure 30 PSI
- Average Cycle Time 57 Seconds
- Loading Height 49.5"
- **Ejector System** Semi-Automatic


HYDRAULIC/ELECTRICAL

- Motor HP 10
- **Voltage 3 Phase** 208, 230, 480
- Full Load Amps 32A, 28A, 14A
- Pump GPM 12/4 HiLo
- Normal System Pressure PSI 2200
- Cylinder Bore 7" x 60"
- **Hydraulic Tank-Capacity Gallons 40**

DIM. (in./mm)

- A. 49.5/1257
- B. 102/2590
- 53.5/1359
- D. 156.5/3975
- 114/2908









- Slotted Front Door
- Wire Guides (allows for front bale tie-off)

COMPACTORSING

- Rear Feed Opening, Front Eiect
- Feed Chute
- Counter Weighted Floppy Retainer Dogs
- Oil Heater
- Weather Proof Package





Due to continual product improvement Compactors Inc. reserves the right to change specifications without notice. The information and pictures used in the document are for illustrative purposes only. Compactors Inc. equipment is ETL/CSA certified with UL listed controls and meets or exceeds ANSI standard Z245.5.

