

REM® HDL-2 HYDRAULIC TOTE LIFT

Lift and dump materials from standard 60 to 95 gallon tote containers with this unique and versatile container lift. This unit is designed for side loading of materials onto the model SC Sorting Conveyors or as a feed for a compactor, shredder, crusher, or other processing equipment. Simply load containers onto the lift and use the convenient foot switch to elevate to an approximate 40 degree tipping angle. The model HDL-2 Hydraulic Tote lift increases worker productivity, reduces back strain and lowers contaminant levels from its very first day of operation.

DURABLE CONSTRUCTION

Built for your most demanding applications, this rugged unit is capable of lifting containers weighing as much as 750 lbs. Containers up to 29" wide can be loaded onto the lift. Discharge heights of up to 60" tall are standard with the availability of custom designs. The unique C-channel and "tube leg" design is built to reinforce the cylinder support blocks and help center the load. An adjustable slide clamp holds the container in place as it tips.




FEATURES

- Helps avoid back strain and injury
- Lifts up to 750 lbs.
- Handles containers up to 29" wide x 48" tall (standard)
- Adjustable retaining slide clamp holds a variety of container sizes
- OSHA-required flow-control valves
- Power-up/gravity-down operation (manual check-valve for return to loading position)
- Forklift pockets for mobility (note: Manufacture requires anchoring your tote to a concrete base for safety)
- Convenient push-to-start/release-to-stop foot switch with 10' cord for operator convenience
- All-steel construction
- 2.5 GPM/2 HP power pack
- Single hydraulic cylinder

DIMENSIONS	HDL
Height	68"
Length	74"
Width	42"
Approx. Weight	900 lbs
Max. Height Raised	10' 6"
Discharge Height	52"

Electrical

- 240/480 volt, three phase
- Electrical components are UL listed
- NEMA-4 (hose proof) enclosure
- Motor overload/short circuit protection
- Custom bucket widths



Due to continual product improvement Compactors Inc. reserves the right to change specifications without notice. The information and pictures used in the document are for illustrative purposes only.