

SCRAP CHOPPER

MODEL 300

“A Tough, Light Duty Scrap Chopper”

The Model 300 scrap chopper is an economical “housekeeping” unit perfect for facilities with lower volumes of scrap materials. This unit is ideal for plastic and steel banding, and other lightweight scrap materials. The Model 300 is designed to fit on several stands that can accommodate a variety of scrap collection containers. **Custom stands and additional safety upgrades are also available.**



MATERIAL REFERENCE

The recommended model of scrap chopper is determined by scrap size, scrap volume, and requested custom features. The following are materials commonly processed through the Model 300. Please consult us to determine the appropriate scrap chopper for your application.

- $\frac{3}{4}$ " x .031" steel banding with clip
- $\frac{5}{8}$ " x .030" plastic/poly straps
- $\frac{3}{4}$ " x .050" plastic/PET straps

CONSTRUCTION FEATURES

- CE version available
- Easy to reach “Feedworks Release” hand lever
- Infeed restrictor plate for safety
- Knives have 4 usable edges and can be rotated (3 times) for extended life
- Made and supported in the USA
- One year warranty

ADD'L SAFETY UPGRADES

- Safety Switches
- Safety Exhaust Spillway Chute
- Machine in Use Light Indicator
- GFCI Plug
- Wash-Down Motor & Electrical
- Sound Dampening
- Auto Starts and Stops
- Timed Stops

OPTIONAL STANDS

- Slider Stand
- Hopper Stand
- Gaylord Stand
- Halsted Bag Adapter Kit for Gaylord Stand

OPTIONAL CONTAINERS

- $\frac{1}{2}$ Yard EZ Dump Hopper

UPGRADES FOR SPECIAL APPLICATIONS

- Split Infeed
- Magnetic Starter
- Frequency Drive
- No Feedworks
- Inverter Duty Motor

PRODUCT SPECIFICATIONS

Electric Motor - $\frac{1}{2}$ HP	Electrical - 1-Phase 120/Volt – 60Hz – 8 amps
Infeed Speed - 123 FPM	Cut Length - 2 $\frac{5}{8}$ "
Infeed Opening - 1" x 1 $\frac{5}{8}$ "	Number of Stationary Knives -1
Number of Rotating Knives - 1	Overall Dimensions - 19" x 30" x 19"
Machine Weight - 136 lbs	Shipping Weight - 220 lbs

Due to continual product improvement Compactors Inc. reserves the right to change specifications without notice. The information and pictures used in the document are for illustrative purposes only.