

INDUSTRIAL HAMMER MILLS **BD SERIES**

High capacity, single rotor, hammer and comb design. Ideal for most deagglomeration applications. Ranging in sizes from laboratory scale to heavy duty industrial, the BD Series Lump Breaker is available in carbon or stainless steel with a hammer and comb design tailored to individual applications. Various rotor speeds are available to optimize performance on a variety of materials reducing dry and/or or hardened agglomerates to a flowable end product.

APPLICATIONS

- Chemicals
- Food Products
- Soda Ash
- Sugar
- Cement

- Resins
- Powder Solubility Improvement

In-line Bulk-solids

BD Series Lump Breaker featuring optional tungsten carbide coated hammers for processing abrasive materials

KEY FEATURES

- High capacity, low energy consumption
- Rugged carbon or stainless steel construction
- Low maintenance, easy to service, readily available parts
- Many grinding rotor configurations available
- V-Belt or gearbox driven
- Hammer and comb arrangement configured to suit application

Model	Standard Inlet	Horsepower	RPM
BD-12x12	12"x12" (305 mm x 305 mm)	5-20 hp (4-15 kW)	500-1000
BD-12x16	12"x16" (305 mm x 410 mm)	5-25 hp (4-19 kW)	500-1000
BD-12x20	12"x20" (305 mm x 510 mm)	10-30 hp (7-22 kW)	500-1000
BD-12x24	12"x24" (305 mm x 610 mm)	10-30 hp (7-22 kW)	500-1000
BD-12x30	12"x30" (305 mm x 760 mm)	15-40 hp (11-30 kW)	500-1000
BD-12x36	12"x36" (305 mm x 915 mm)	15-40 hp (11-30 kW)	500-1000
BD-16x16	16"x16" (406 mm x 406 mm)	10-30 hp (7-22 kW)	500-900

Model	Standard Inlet	Horsepower	RPM
BD-16x20	16"x20" (406 mm x 510 mm)	10-30 hp (7-22 kW)	500-900
BD-16x24	16"x24" (406 mm x 610 mm)	15-30 hp (11-22 kW)	500-900
BD-16x36	16"x36" (406 mm x 915 mm)	20-30 hp (15-22 kW)	500-900
BD-20x20	20"x20" (510 mm x 510 mm)	15-25 hp (11-19 kW)	500-700
BD-20x30	20"x30" (510 mm x 760 mm)	15-25 hp (11-19 kW)	500-700
BD-20x36	20"x36" (510 mm x 915 mm)	20-30 hp (15-22 kW)	500-700
BD-20x48	20"x48" (510 mm x 1220 mm)	20-30 hp (15-22 kW)	500-700
BD-20x60	20"x60" (510 mm x 1525 mm)	30-50 hp (22-37 kW)	500-700

Due to continual product improvement Compactors Inc. reserves the right to change specifications without notice. The information and pictures used in the document are for illustrative purposes only.

