


WASTE MANAGEMENT SYSTEMS



Models

**TA3000SS, TA4500SS,
TA7000SS**

**One full year
limited warranty**



Model TA4500SS

Model TA7000SS

Model TA3000SS


Perfect for Marine & Offshore Industries

Standard Features – Stainless Steel Cabinet & Compaction Chamber

- All stainless steel exterior
- All stainless steel compaction chamber
- Heavy duty welded construction
- Push button controls
- Multi-operational key switch
- UL Listed Components
- Compaction ratios up to 20:1
- UV Germicidal unit for odor control & to eliminate bacteria, viruses & harmful contaminants
- Reusable split trashcube
- Safety interlock system
- Heavy duty compaction plate
- Modular electrical system
- Two stage hydraulic pump
- Trashcube ejector system
- Baling Capabilities: Cardboard & Packaging Materials
- Bag dispenser
- Full indicator, buzzer & light
- Heavy duty deck legs

Specifications

	Series TA3000SS	Series TA4500SS	Series TA7000SS
Height – A	71 ¼"	77 ¾"	80 ¼"
Width – B	22 ¼"	28 ¼"	40 ¼"
Depth – C	22 ¼"	28"	28"
Service Weight	700 lbs.	900 lbs.	1,200 lbs.
Loading Chute Door Opening	15 ¼" x 18"	19" x 24"	20 ½" x 36"
Compaction Chamber Size	37 ½" x 18 ¾" x 18 ¼"	40 ½" x 24" x 24"	41 ¾" x 36" x 24"
Capacity	3.3 cu. ft. Ratios to 20:1	6 cu. ft. Ratios to 20:1	9 cu. ft. Ratios to 20:1
Cycle Time	11 – 15 seconds	18 – 22 seconds	20 – 25 seconds
Motor Size	½ hp	½ hp	1 hp
Electrical Requirements	120 or 240 volts 9/4.5 amps	120 or 240 volts 9/4.5 amps	120 or 240 volts 14/7 amps
Max. Comp. Force	8,640 lb.	13,500 lb.	24,000 lb.
Working Space	46" x 22"	54" x 30"	66" x 42"



PO Box 3173
Hilton Head Island, SC 29928

800-423-4003
843-686-5503
843-686-3290 (fax)

www.CompactorsInc.com
info@CompactorsInc.com