



OEG ENVIRO-PAK® OFFSHORE C-SERIES COMPACTORS & BALERS

- Meets and exceeds International MARPOL 73/78 Annex V
- Filter/can/glass crusher and food grind attachment available
- Slow release door for easy bag removal
- Functions as both a compactor and a baler
- Moving parts completely enclosed to prevent injury
- Hydraulic operated roll back top for easy loading and unloading
- Compacts all types of non-hazardous waste into bag
- In bag compaction at a 5:1 safety ratio
- Two hand operation for operator safety
- Reduce disposal costs by reducing waste volume
- UL listed components
- ABS approved
- Patented



TECHNICAL SPECIFICATIONS

Due to continual product improvement Compactors Inc. reserves the right to change specifications without notice. The information and pictures used in the document are for illustrative purposes only.

Unit	Model 3000C	Model 4000C	Model 5000C	Model 3000CC	Model 4000CB	Model 5000CC
Capacity	30 ft³ x 0.9 m³	40 ft³ x 1.1 m³	50 ft³ x 1.42 m³	60 ft³ x 1.7 m³	70 ft³ x 2 m³	80 ft³ x 2.3 m³
Height	107" / 2718 mm	107" / 2718 mm	114" / 2896 mm	107" / 2718 mm	108" / 2743 mm	108" / 2743 mm
Width	56" / 1422 mm	62" / 1575 mm	62" / 1575 mm	56" / 1422 mm	62" / 1575 mm	62" / 1575 mm
Depth	83" / 2108 mm	89" / 2261 mm	95" / 2413mm	83" / 2108 mm	89" / 2261 mm	91" / 2311 mm
Deck Space	32 ft² / 3.0 m²	38 ft² / 3.5 m²	38 ft² / 3.5 m²	32 ft² / 3.0 m²	38 ft² / 3.5 m²	39 ft² / 3.6 m²
Weight	3,900 lbs / 1,772 kg	4,115 lbs / 1,867 kg	4,360 lbs / 1,982 kg	4,450 lbs / 2,018 kg	4,850 lbs / 2,200 kg	4,850 lbs / 2,200 kg
Compaction Force	60,000 lbs / 27,216 kg	60,000 lbs / 27,216 kg	60,000 lbs / 27,216 kg	60,000 lbs / 27,216 kg	60,000 lbs / 27,216 kg	60,000 lbs / 27,216 kg
Bag Model	HV96026	HV96030	HV96027	HV96026	HV96030	HV96027
Bag SWL	1,500 lbs / 680 kg	2,200 lbs / 997 kg	2,200 lbs / 997 kg	1,500 lbs / 680 kg	2,200 lbs / 997 kg	2,200 lbs / 997 kg
Electrical Rating	5 HP 230/460V 7.8/15.5 AMPS	5 HP 230/460V 7.8/15.5 AMPS	5 HP 230/460V 7.8/15.5 AMPS	5 HP 230/460V 7.8/15.5 AMPS	5 HP 230/460V 7.8/15.5 AMPS	5 HP 230/460V 7.8/15.5 AMPS
Air Requirement	100 PSI / 75 CFM	100 PSI / 75 CFM	100 PSI / 75 CFM	100 PSI / 75 CFM	100 PSI / 75 CFM	100 PSI / 75 CFM
Cycle Time	96 seconds	96 seconds	96 seconds	96 seconds	96 seconds	96 seconds
Oil Capacity	10 GAL / 38 L	10 GAL / 38 L	10 GAL / 38 L	10 GAL / 38 L	10 GAL / 38 L	10 GAL / 38 L