



OEG ENVIRO-PAK® OFFSHORE
H-SERIES COMPACTORS & BALERS

- Meets and exceeds International MARPOL 73/78 Annex V
- ABS approved
- Baling capabilities available upon request
- Safety switch on door prevents operation
- Air or electric operation
- Door with latch engineered for gradual release
- Compacts all types of non-hazardous waste
- 100% stainless steel structure
- Component parts are sand blasted and painted
- Bags manufactured to a 5:1 safety ratio
- Two hand operation for operator safety
- Manual operation is standard
- Improve shipboard incinerator efficiency and reduce operating time by compacting waste prior to incineration
- UL listed components
- Patent Pending



Due to continual product improvement Compactors Inc. reserves the right to change specifications without notice. The information and pictures used in the document are for illustrative purposes only.

TECHNICAL SPECIFICATIONS

Unit	Model H2	Model H5	Model H10	Model H15
Capacity	6 ft³ x 0.2 m³	20 ft³ x 0.57 m³	40 ft³ x 1.1 m³	50 ft³ x 1.4 m³
Height	79" / 2006 mm	90" / 2286 mm	120" / 3048 mm	128" / 3251 mm
Width	32" / 813 mm	46" / 1168 mm	49" / 1245 mm	52" / 1320 mm
Depth	27" / 686 mm	48" / 1219 mm	55" / 1397 mm	58" / 1473 mm
Deck Space	6 ft² / 0.6 m²	15 ft² / 1.4 m²	19 ft² / 1.8 m²	21 ft² / 2.0 m²
Maintenance Space	12 ft² / 1.1 m²	56 ft² / 5.2 m²	60 ft² / 5.5 m²	63 ft² / 5.8 m²
Weight	520 lbs / 236 kg	1,615 lbs / 733 kg	1,930 lbs / 876 kg	2,100 lbs / 952 kg
Compaction Force	10,000 lbs / 4536 kg	28,000 lbs / 12701 kg	40,000 lbs / 18144 kg	40,000 lbs / 18144 kg
Bag Part Number	HV96033	HV96025	HV96030	HV96027
Bag SWL	650 lbs / 295 kg	1,000 lbs / 454 kg	2,200 lbs / 997 kg	2,200 lbs / 997 kg
Electrical Rating	2 HP 210/230/480V 4/5.8/2.9 AMPS	3 HP 230/460V 7.8/2.9 AMPS	3 HP 230/460V 7.8/2.9 AMPS	3 HP 230/460V 7.8/2.9 AMPS
Air Requirement	100 PSI / 75 CFM	100 PSI / 75 CFM	100 PSI / 75 CFM	100 PSI / 75 CFM
Cycle Time	35 seconds	50 seconds	95 seconds	95 seconds
Oil Capacity	1.5 GAL / 5.6 L	2.5 GAL / 9.5 L	10 GAL / 38 L	10 GAL / 38 L