

VERTICAL DOWNSTROKE BALER

MODEL 3600HDLP

A popular high density downstroke 60" baler, the 3600HDLP is constructed with heavy duty structural steel and fits under an 8-foot ceiling. It's designed for supermarkets, retail chains, hospitals, hotels and malls.



SPECIFICATIONS

Baler Dimensions (W x D x H): 94 ½" x 51 ¾" x 95 ½"

Feed Height: 33"

Baler Chamber (D x H): 36" x 46"

Bale Weight: 600-800 lbs OCC

Bale Dimensions (W x D x H): 60" x 36" x 30"

Pump: 10.5 gpm

Control Voltage: 110 – 120 vac

Electric: 208 / 230 / 460 – 3 phase

Shipping Weight: 4,720 lbs

Cylinder Bore: 6"

Cylinder Rod: 3 1/2"

Rod Stroke: 27"

Average Cycle Time: 32 seconds

Motor: 10 HP

Working Pressure: 2,400 PSI

Relief Pressure: 2,700 PSI

Working Force: 67,858 lbs

Relief Force: 76,341 lbs

Nor Ram Pressure: 32.7 PSI

Max Ram Pressure: 36.7 PSI

Due to continual product improvement Compactors Inc. reserves the right to change specifications without notice. The information and pictures used in the document are for illustrative purposes only.