

VERTICAL DOWNSTROKE BALER

MODEL 420HD

This small but powerful machine has been specifically engineered for applications with limited space or budget. The 420HD series has all of the important safety features that make it a leader in the vertical baler industry. It's designed for supermarkets, retail chains, hospitals, hotels and malls.



SPECIFICATIONS

Baler Dimensions (W x D x H): 54 1/4" x 29 1/2" x 95 3/4"
Feed Height: 32 3/4"
Baler Chamber (D x H): 24" x 30"
Bale Weight: 200-400 lbs OCC
Bale Dimensions (W x D x H): 42" x 24" x 30"
Pump: 3.2 gpm

Control Voltage: 110 – 120 vac
Electric: 208 / 230 / 460 – 3 phase
Shipping Weight: 1,440 lbs
Cylinder Bore: 4"
Cylinder Rod: 2 1/2"
Rod Stroke: 32"
Average Cycle Time: 53 seconds

Motor: 3 HP
Working Pressure: 1,600 PSI
Relief Pressure: 1,900 PSI
Working Force: 20,100 lbs
Relief Force: 23,870 lbs
Nor Ram Pressure: 19.7 PSI
Max Ram Pressure: 23.4 PSI

Due to continual product improvement Compactors Inc. reserves the right to change specifications without notice. The information and pictures used in the document are for illustrative purposes only.