

VERTICAL DOWNSTROKE BALER

MODEL 2300HD

This most popular high density downstroke 60" baler, the 2300HD is constructed with heavy duty structural steel and produces bales up to 1,100 lbs. Designed for warehouses, retail chains, distribution centers and manufacturing plants.



SPECIFICATIONS

Baler Dimensions (W x D x H): 78" x 41" x 152"

Feed Height: 54 3/4"

Baler Chamber (D x H): 30" x 48"

Bale Weight: 850-1000 lbs OCC

Bale Dimensions (W x D x H): 60" x 30" x 48"

Pump: 10.5 gpm

Control Voltage: 110 – 120 vac

Electric: 208 / 230 / 460 – 3 phase

Shipping Weight: 4,510 lbs

Cylinder Bore: 6"

Cylinder Rod: 3 1/2"

Rod Stroke: 48"

Average Cycle Time: 56 seconds

Motor: 10 HP

Working Pressure: 2,000 PSI

Relief Pressure: 2,300 PSI

Working Force: 56,538 lbs

Relief Force: 65,019 lbs

Nor Ram Pressure: 30.9 PSI

Max Ram Pressure: 35.5 PSI

Due to continual product improvement Compactors Inc. reserves the right to change specifications without notice. The information and pictures used in the document are for illustrative purposes only.